

i30 COMMERCIAL ICE AND WATER DISPENSER



Innovative Features & Technology

- Combination nugget-style ice and water dispenser
- Capacitive touch sensor activation
- Available with optional base cabinet
- LED UV at point of dispense



Easy Maintenance Design

- High clearance stainless steel legs
- Smooth front surface for quick and easy cleaning
- High capacity drip tray prevents spills



Reliable & Dependable Components

- 30 lb. capacity stainless steel ice bin
- Ice production:
 - 380lbs/day @ 70F air + 50F water
 - 289lbs/day @ 90F air + 70F water
- Ventilation on top of unit allows freedom of placement



i30 COMMERCIAL ICE AND WATER DISPENSER



Description

Specification

Unit Weight

223 lbs.

Unit Dimensions

46.1"h x 16.6"w x 26.7"d

Base Cabinet Dimensions

28.3"h x 16.6"w x 26.7"d

Dispense Height

10.5"

Water Temperature

Ambient

Description

Specification

Daily Ice Production

380lbs/day @ 70F air + 50F water
289lbs/day @ 90F air + 70F water

Ice Bin Capacity

30 lbs.

Recommended Water Pressure

30-60 psi

Rated Voltage/Frequency

115v/60hz

Power Consumption

8.8A Nominal

wellsys®

www.wellsyswater.com

630 Allendale Road, Suite 200
King of Prussia, PA 19406
855.558.9796

Tested and certified



The Wellsys i30 systems are certified by IAPMO R&T against NSF/ANSI/CAN 61: Qs1, NSF/ANSI/CAN 372 and CSA B483.1 for the specific performance of material safety, structural integrity, and lead-free requirements as verified and substantiated by the test data. The W5-UF System is also certified to NSF/ANSI-42 for the reduction of Chlorine and Taste & Odor when using the Wellsys WPC-12 filter. The Wellsys W5-RO system, when used with the WPC-12 and WRO-1280 or WRO-12150 filters, is also certified by IAPMO R&T to NSF/ANSI 58 for the reduction of the following substances, as verified and substantiated by test data: Chlorine, Taste & Odor, Pentavalent Arsenic (less than 50ppb reduction), Cyst, Lead, Total PFAS, TDS, and Turbidity.

Do not use with water that is micro-biologically unsafe or of unknown quality without adequate disinfection before or after the system.